


Features:

- M18*1 mm , Full stainless steel housing;
- 5/8mm , flush mountable;
- DC 3-wire , switching output;
- Cable




Dimensioned drawing



Model No.

Sensing range	Sn:5 mm	Sn:8 mm
NPN N.O	SIMF-M18-05N-V11-PV2	SIMF-M18-08N-V11-PV2
NPN N.C	SIMF-M18-05N-V21-PV2	SIMF-M18-08N-V21-PV2
PNP N.O	SIMF-M18-05P-V11-PV2	SIMF-M18-08P-V11-PV2
PNP N.C	SIMF-M18-05P-V21-PV2	SIMF-M18-08P-V21-PV2

Mounting



Sn	D1	D2	D3
M1805	≥0	≥18	≥18
M1808	≥2.5	≥18	≥18

⚠ Tightening torque of the fastening screws: <40Nm!

Correction Factor	Factor
Non-ferrous metal	1
Fe360	1
Aluminum	0.35~0.45
Brass	0.35~0.5
Copper	0.25~0.45
Stainless steel	0.6~1.0
Cast Iron	0.93~1.05
Nickel	0.65~0.75

Technical data

Electrical data	Operating voltage	10-30V DC
	Switching frequency	100Hz
	Voltage drop	≤2.0V
	Leakage current	<0.01mA
	Load current	200mA
	No load current	≤10mA(24V)
	Hysteresis	<15%(Sr)
	Repeatability	<1.0%(Sr)
	Temperature drift	<10%(Sr)
	Short circuit protection	Yes
	Overload protection	Yes
	Polarity reversal protection	Yes
Environment	Ambient temperature	-25...70°C
	Ingress protection	IP67
Mechanical data	Housing material	Stainless steel
	Face material	Stainless steel
Electrical connection	Connectors	PVC cable/2m,3*0.35mm ²

Wiring

